





TS202



SPECIFICAIONS:




Rating: DC30V 1A ;
Contact resistance: 100m Ω (Max.) ;
Insulation resistance: DC500V 100M Ω (Min.) ;
Withstand voltage: AC 1000V for 1 minute ;
Operating force: 700 $\pm$ 150g ;
Life cycle: 20,000 cycles ;
Total Travel: 1.5 $\pm$ 0.3 mm .

MATERIAL:

Frame:Nylon66,UL rated:94V-2 Min. ;
Cap:POM ;
Terminal:Brass,Silver or Tin plated .

Function:

ON(P-6)-OFF-ON (P-1)-OFF



P.C.B. LAYOUT

X	Cap Color
R	Red 红色
Y	Yellow 黄色
G	Green 绿色
B	Black 黑色
U	Blue 蓝色
W	White 白色
A	Gray 灰色

				公差 TOLEANCES		.X $\pm$ 0.3	.XX $\pm$ 0.15	角度	$\pm$ 1°	单位 DIMENSION UNIT mm.	
				版本	A1	比例尺	NONE	日期	2020.07.15	品名	图号
				VERSION		SCALE		DATE		TITLE	DRAWING NO
				核准		核对	Z. H. B.	绘图	王立权	TS202-21-4-B(高柄)	TS202-21-4-B_A1
版本 VER.	变更说明	CHANGE DESCRIPTION	日期 DATE	ECN NO.	APPROVED BY	CHECKED BY		DRAWN BY			