






Specifications	
Circuit	:SPST
Current rating	:50mA
Voltage rating	:12VDC
Dielectric withstanding voltage	:250VAC for 1 minute
Contact resistance	:100m Ω Max. (Initial)
Insulation resistance	:100M Ω Min.
Operating force	:300 $\pm$ 50gf
	:200 $\pm$ 50gf
Total travel	:0.25mm $\pm$ 0.1mm
Operating life	:100,000 cycles Min
Solder specifications	:260° C for 5 seconds
Function	:Momentary
Operating temperature	:+10° C ~ +60° C

P.C.B. LAYOUT



CIRCUIT



MATERIAL:

Base Frame: Nylon46, UL rated:94 V-2 Min. ;
Outer Frame: Nylon66, UL rated:94 V-2 Min. ;
Actuator: PBT, UL rated:94 V-2 Min. ;
Cap: ABS ;
Terminal: Brass, Silver or Tin plated .

				公差 TOLERANCES	.X $\pm$ 0.3	.XX $\pm$ 0.15	角度 ANGLE	$\pm$ 1°	单位	DIMENSION UNIT	mm.
				版本	A2	比例尺	NONE	日期	2019.10.16	品名	TITLE
A2	重新整理后发行	2019.10.16	N/A	VERSION		SCALE		DATE			图号
A1	重新整理后发行	2014.07.17	N/A	核准		核对		绘图	王立权	TS2-1B-1AN	DRAWING NO
版本 VER.	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.	APPROVED BY		CHECKED BY		DRAWN BY			TS2-1B-1AN_A2